



<table border="1"> <tr> <td>Product Name</td> </tr> <tr> <td>CO.ACRYL</td> </tr> <tr> <td>Technical Name</td> </tr> <tr> <td>Flat smooth finish Vinyl Emulsion</td> </tr> <tr> <td>Key Properties</td> </tr> <tr> <td> <ul style="list-style-type: none"> • Manufactured to conform to BS7719: 1994 specification for water-borne emulsion, Type A. • Washable • Very good hiding power and opacity, very good durability. • Low water absorption • CO.ACRYL offers enhanced resistance to flame spread. • Very low VOC content • Odorless • Over 100,000 colors available through the automated tinting system. </td> </tr> <tr> <td>Recommended Uses</td> </tr> <tr> <td>Internal & external applications</td> </tr> <tr> <td>Type of Substrate</td> </tr> <tr> <td>Plaster, embossed wall coverings, gypsum board, concrete, cement rendering, brickwork & block work</td> </tr> <tr> <td>Finish</td> </tr> <tr> <td>Flat 1/10</td> </tr> <tr> <td>Coverage</td> </tr> <tr> <td>Approximately 10-11 square meters per liter.</td> </tr> <tr> <td>Drying Time</td> </tr> <tr> <td>Touch-dry in 1/2-1 hour Re-coatable after 2-4 hours</td> </tr> </table>	Product Name	CO.ACRYL	Technical Name	Flat smooth finish Vinyl Emulsion	Key Properties	<ul style="list-style-type: none"> • Manufactured to conform to BS7719: 1994 specification for water-borne emulsion, Type A. • Washable • Very good hiding power and opacity, very good durability. • Low water absorption • CO.ACRYL offers enhanced resistance to flame spread. • Very low VOC content • Odorless • Over 100,000 colors available through the automated tinting system. 	Recommended Uses	Internal & external applications	Type of Substrate	Plaster, embossed wall coverings, gypsum board, concrete, cement rendering, brickwork & block work	Finish	Flat 1/10	Coverage	Approximately 10-11 square meters per liter.	Drying Time	Touch-dry in 1/2-1 hour Re-coatable after 2-4 hours	<table border="1"> <tr> <td>Thinner</td> </tr> <tr> <td>Clean water Thin up to 10%-15% for the first coat. Thin up to 20%-30% for the following coats.</td> </tr> <tr> <td>Preparation</td> </tr> <tr> <td>All surfaces to be painted should be clean, dry and free from loose & flaking material. Rub down & rinse. Prime with Colors Stabilizers where necessary.</td> </tr> <tr> <td>Instructions</td> </tr> <tr> <td>Stir well. Easy to apply by brush, roller or airless spray. Do not apply at temperatures below 5C or when rain is expected.</td> </tr> <tr> <td>Cleaning</td> </tr> <tr> <td>Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water & rinse thoroughly. Do not empty product into drains or watercourses.</td> </tr> <tr> <td>Additional Info</td> </tr> <tr> <td> <ul style="list-style-type: none"> • Contains no added lead • Product batches are tested using a quality control system. • Adhesion 0.5N/mm² based on ASTM D4541 • Scrubability higher than 1000 cycles based on ASTM D4213 conforms to Libnor 1999:84&83 for external emulsion paint </td> </tr> <tr> <td>Pack Size</td> </tr> <tr> <td> <ul style="list-style-type: none"> • 1US Quart – (0.945 liters) • 1US Gallon – (3.785 liters) • 1US Drum – (18.925 liters) </td> </tr> <tr> <td>Transportation & Storage</td> </tr> <tr> <td>Care should be taken to avoid spillage. Protect from frost & humidity.</td> </tr> </table>	Thinner	Clean water Thin up to 10%-15% for the first coat. Thin up to 20%-30% for the following coats.	Preparation	All surfaces to be painted should be clean, dry and free from loose & flaking material. Rub down & rinse. Prime with Colors Stabilizers where necessary.	Instructions	Stir well. Easy to apply by brush, roller or airless spray. Do not apply at temperatures below 5C or when rain is expected.	Cleaning	Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water & rinse thoroughly. Do not empty product into drains or watercourses.	Additional Info	<ul style="list-style-type: none"> • Contains no added lead • Product batches are tested using a quality control system. • Adhesion 0.5N/mm² based on ASTM D4541 • Scrubability higher than 1000 cycles based on ASTM D4213 conforms to Libnor 1999:84&83 for external emulsion paint 	Pack Size	<ul style="list-style-type: none"> • 1US Quart – (0.945 liters) • 1US Gallon – (3.785 liters) • 1US Drum – (18.925 liters) 	Transportation & Storage	Care should be taken to avoid spillage. Protect from frost & humidity.
Product Name																															
CO.ACRYL																															
Technical Name																															
Flat smooth finish Vinyl Emulsion																															
Key Properties																															
<ul style="list-style-type: none"> • Manufactured to conform to BS7719: 1994 specification for water-borne emulsion, Type A. • Washable • Very good hiding power and opacity, very good durability. • Low water absorption • CO.ACRYL offers enhanced resistance to flame spread. • Very low VOC content • Odorless • Over 100,000 colors available through the automated tinting system. 																															
Recommended Uses																															
Internal & external applications																															
Type of Substrate																															
Plaster, embossed wall coverings, gypsum board, concrete, cement rendering, brickwork & block work																															
Finish																															
Flat 1/10																															
Coverage																															
Approximately 10-11 square meters per liter.																															
Drying Time																															
Touch-dry in 1/2-1 hour Re-coatable after 2-4 hours																															
Thinner																															
Clean water Thin up to 10%-15% for the first coat. Thin up to 20%-30% for the following coats.																															
Preparation																															
All surfaces to be painted should be clean, dry and free from loose & flaking material. Rub down & rinse. Prime with Colors Stabilizers where necessary.																															
Instructions																															
Stir well. Easy to apply by brush, roller or airless spray. Do not apply at temperatures below 5C or when rain is expected.																															
Cleaning																															
Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water & rinse thoroughly. Do not empty product into drains or watercourses.																															
Additional Info																															
<ul style="list-style-type: none"> • Contains no added lead • Product batches are tested using a quality control system. • Adhesion 0.5N/mm² based on ASTM D4541 • Scrubability higher than 1000 cycles based on ASTM D4213 conforms to Libnor 1999:84&83 for external emulsion paint 																															
Pack Size																															
<ul style="list-style-type: none"> • 1US Quart – (0.945 liters) • 1US Gallon – (3.785 liters) • 1US Drum – (18.925 liters) 																															
Transportation & Storage																															
Care should be taken to avoid spillage. Protect from frost & humidity.																															

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.
Tel: 961 1 303414-305649-306966-819672 Beirut-Lebanon. Fax: 961-1-816428. E-mail: kassaa@kassaa.com .