



<b>Product Name</b> CO.SUPER flat	<b>Preparation</b> All surfaces to be painted should be clean, dry and free from loose & flaking material. Rub and prime for wood surfaces with undercoat (stabilizers range) for metals with zinc-chromate, zinc-phosphate or red oxide (oxford protective coatings).
<b>Technical Name</b> Smooth Flat Enamel Finish Synthetic Alkyd Enamel	
<b>Key Properties</b> <ul style="list-style-type: none"> <li>• Very attractive flat finish</li> <li>• Unleaded</li> <li>• Highly washable &amp; durable</li> <li>• Superior adhesion to substrates</li> <li>• Very good hiding power and opacity</li> <li>• Excellent color retention</li> <li>• Over 100,000 colors available through the automated tinting system</li> </ul>	<b>Instructions</b> Stir well. Easy to apply by brush, roller or airless spray. Do not apply when rain is expected.
<b>Recommended Uses</b> Internal & external applications	<b>Cleaning</b> Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly. Do not empty product into drains or watercourses.
<b>Type of Substrate</b> Wood & metal. Plaster, wallboards, concrete, cement rendering, brick work & block work etc.	<b>Additional Info</b> Product batches are tested using a quality control system. CO.SUPER flat is a low odor product.
<b>Finish</b> Flat finish 1/10	<b>Pack Size</b> <ul style="list-style-type: none"> <li>• 1US Quart – (0.945 liters).</li> <li>• 1US Gallon – (3.785 liters).</li> </ul>
<b>Coverage</b> Approximately 10-12 square meters per liter.	<b>Transportation &amp; Storage</b> Care should be taken to avoid spillage. Protect from frost & humidity.
<b>Drying Time</b> Touch-dry in 3-6 hours Re-coatable after 16-24 hours	
<b>Thinner</b> White spirit , CO.SUPER flat could be also diluted with thinner to shorten the drying time. Thin up to 10%-20%	

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.  
 Tel: 961 1 303414-305649-306966-819672 Beirut-Lebanon . Fax: 961-1-816428 . E-mail: [kassaa@kassaa.com](mailto:kassaa@kassaa.com) .