

**Product Name**

CO.SUPER gloss

Technical Name

Full Gloss Enamel Finish
Synthetic Alkyd Enamel

Key Properties

- A top quality gloss
- Unleaded
- Highly washable & superior durability
- Superior adhesion to substrates
- Superior hiding power and opacity
- Excellent color retention
- Over 100,000 colors available through the automated tinting system

Recommended Uses

Internal & external applications

Type of Substrate

Wood & metal. Plaster, wallboards, concrete, cement rendering, brick work & block work etc.

Finish

Full gloss 9/10

Coverage

Approximately 10-12 square meters per liter.

Drying Time

Touch-dry in 3-6 hours
Re-coatable after 16-24 hours

Thinner

White spirit, CO.SUPER gloss could be also diluted with thinner to shorten the drying time.
Thin up to 10%-20%

Preparation

All surfaces to be painted should be clean, dry and free from loose & flaking material. Rub and prime for wood surfaces with undercoat (stabilizers range) for metals with zinc-chromate, zinc-phosphate or red oxide (oxford protective coatings).

Instructions

Stir well. Easy to apply by brush, roller or airless spray.
Do not apply when rain is expected.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly.
Do not empty product into drains or watercourses.

Additional Info

Product batches are tested using a quality control system.
CO.SUPER gloss is a low odor product.

Pack Size

- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).

Transportation & Storage

Care should be taken to avoid spillage.
Protect from frost & humidity.

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.

Tel: 961 1 303414-305649-306966-819672 Beirut-Lebanon. Fax: 961-1-816428. E-mail: kassaa@kassaa.com.