



### Product Name

CO.SUPER semi gloss

### Technical Name

Semi Gloss Enamel Finish  
Synthetic Alkyd Enamel

### Key Properties

- Very attractive semi gloss finish
- Unleaded
- Highly washable & superior durability
- Superior adhesion to substrates
- Superior hiding power and opacity
- Excellent color retention
- Over 100,000 colors available through the automated tinting system

### Recommended Uses

Internal & external applications

### Type of Substrate

Wood & metal, plaster, wallboards, concrete, cement rendering, brick work & block work etc.

### Finish

Semi gloss finish 5/10

### Coverage

Approximately 10-12 square meters per liter.

### Drying Time

Touch-dry in 3-6 hours  
Re-coatable after 16-24 hours

### Thinner

White spirit, CO.SUPER semi gloss could be also diluted with thinner to shorten the drying time.  
Thin up to 10%-20%

### Preparation

All surfaces to be painted should be clean, dry and free from loose & flaking material. Rub and prime for wood surfaces with undercoat (stabilizers range) for metals with zinc-chromate, zinc-phosphate or red oxide (oxford protective coatings).

### Instructions

Stir well. Easy to apply by brush, roller or airless spray.  
Do not apply when rain is expected.

### Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly.  
Do not empty product into drains or watercourses.

### Additional Info

Product batches are tested using a quality control system.  
CO.SUPER semi gloss is a low odor product.

### Pack Size

- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).

### Transportation & Storage

Care should be taken to avoid spillage.  
Protect from frost & humidity.