



<p><b>Product Name</b> GLAZE water-borne</p>	<p><b>Thinner</b> No thinning is required.</p>
<p><b>Technical Name</b> Effect finish</p>	<p><b>Preparation</b> All surfaces to be painted should be clean, dry and free from loose &amp; flaking material. Rub down &amp; rinse. Prime the substrate with UNDERCOAT, colors oil-based paints or colors CO.SHEEN to block substrates' absorption.</p>
<p><b>Key Properties</b></p> <ul style="list-style-type: none"> <li>• Unleaded</li> <li>• Water based</li> <li>• Washable (after full curing)</li> <li>• Non-flammable</li> <li>• Odorless</li> <li>• Very low VOC content</li> <li>• Over 100,000 colors available through the automated tinting system.</li> </ul>	<p><b>Instructions</b> Stir well Easy application by any effect tool for dragging, sponging, graining, sponging, marbling, stippling ... techniques Do not apply at temperatures below 5C or when rain is expected.</p>
<p><b>Recommended Uses</b> Internal &amp; external applications</p>	<p><b>Cleaning</b> Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water &amp; rinse thoroughly. Do not empty product into drains or watercourses.</p>
<p><b>Type of Substrate</b> Plaster, embossed wall coverings, gypsum board, concrete, cement rendering, brickwork &amp; block work</p>	<p><b>Additional Info</b> Product batches are tested using a quality control system.</p>
<p><b>Finish</b> Decorative finish dependant on the application procedure</p>	<p><b>Pack Size</b></p> <ul style="list-style-type: none"> <li>• 1US Quart – (0.945 liters)</li> <li>• 1US Gallon – (3.785 liters)</li> <li>• 1US Drum – (18.925 liters)</li> </ul>
<p><b>Coverage</b> Approximately 85 grams per square meter</p>	<p><b>Transportation &amp; Storage</b> Care should be taken to avoid spillage. Protect from frost &amp; humidity.</p>
<p><b>Drying Time</b> Open drying time ± 15min Open drying time can be extended up to one hour using "Classic color"</p>	

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.  
Tel: 00961 1 303414-305649-306966-819672 Beirut-Lebanon. Fax: 961-1-816428. E-mail: [kassaa@kassaa.com](mailto:kassaa@kassaa.com) .