



Product Name

PRIMER

Technical Name

Universal primer
Vinyl water based

Key Properties

- Ideal as a primer for water based finishes
- Colors PRIMER is odorless
- Formulated for application to surfaces of a highly porous or friable nature
- Superior adhesion to all kinds of substrates
- High resin content
- Very good hiding power and opacity, very good durability
- Very low water absorption
- Offers enhanced resistance to flame spread
- Very low VOC content
- Over 100,000 colors available through the automated tinting system.

Recommended Uses

Internal & external applications

Type of Substrate

Plaster, wall coverings, wall paper, cement, gypsum board, concrete, wood rendering, brickwork & block work etc.

Finish

Dries satin to form an excellent bond for subsequent coats

Coverage

Approximately 10-11 square meters per liter.

Drying Time

Touch-dry in 15 minutes
Re-coatable after 0.5 to 1 hour

Thinner

Clean water
Thin up to 15%-35%

Preparation

All surfaces to be painted should be clean, dry and free from loose & flaking material. Rub down & prime.

Instructions

Stir well. Easy to apply by brush, roller or airless spray.
Do not apply at temperatures below 5C or when rain is expected.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water & rinse thoroughly.
Do not empty product into drains or watercourses.

Additional Info

- Product batches are tested using a quality control system.

Pack Size

- 1US Quart – (0.945 liters)
- 1US Gallon – (3.785 liters)
- 1US Drum – (18.925 liters)

Transportation & Storage

Care should be taken to avoid spillage.
Protect from frost & humidity.

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.
Tel: 00961 1 303414-305649-306966-819672 Beirut-Lebanon. Fax: 961-1-816428. E-mail: kassaa@kassaa.com .