



Product Name

STAIN wood dye

Technical Name

Penetrating wood dye
Solvent based solution

Key Properties

- Unleaded
- UV resistant contains a special light stabilizer for enhanced protection against harsh atmospheric exposure should be covered by a top coat
- superior color durability, fading and yellowing resistance
- 72 attractive wood colors available through the automated tinting system.

Recommended Uses

Internal & external applications

Type of Substrate

Smooth, planed softwood & hardwood...

Finish

Wood stain is not a finishing product

Coverage

Approximately 20 square meters per liter dependant on the type of treated wood.

Drying Time

15 minutes

Thinner

White spirit.
Dilution will highly affect the final shade.
The higher the dilution ratio the lighter the color will be.

Preparation

The final color will be highly affected with the treated wood color.

In some cases (dark wood) a bleaching process might be necessary to obtain the required color.

Instructions

Stir well. Easy to apply by roller, brush, spray or airless spray, STAIN wood dye can be applied using a rag or a sponge.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly.

Do not empty product into drains or watercourses.

Additional Info

Product batches are tested using a quality control system.

Colors STAIN wood dye is a low odor product.

Pack Size

- 1US Quart – (0.945 liters)

Transportation & Storage

Care should be taken to avoid spillage.

Protect from frost & humidity.

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.

Tel: 961 1 303414-305649-306966-819672 Beirut-Lebanon . Fax:961-1-816428 . e-mail: kassaa@kassaa.com .