



<p>Product Name UNDERCOAT</p>	<p>Preparation All surfaces to be painted should be clean, dry and free from loose & flaking material. Rub down & prime.</p>
<p>Technical Name Universal penetrating primer Synthetic Alkyd solvent based</p>	<p>Instructions Stir well. Easy to apply by brush, roller or airless spray. Do not apply at temperatures below 5C or when rain is expected.</p>
<p>Key Properties</p> <ul style="list-style-type: none"> • Ideal as a primer for all water and oil based finishes • Unleaded • Colors UNDERCOAT is a low odor product • Superior adhesion to all kinds of substrates • Based on a high quality synthetic alkyd resin • Superior hiding power and opacity , superior durability • Low absorption 	<p>Cleaning Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly. Do not empty product into drains or watercourses.</p>
<p>Recommended Uses Internal & external applications</p>	<p>Additional Info</p> <ul style="list-style-type: none"> • Product batches are tested using a quality control system • Adhesion 0.5N/mm2 based on ASTM D4541 • Scrubability higher than 1000 cycles based on ASTM D4213
<p>Type of Substrate Wood, metal and Plaster, wallboards, concrete, cement rendering, brick work & block work etc.</p>	<p>Pack Size</p> <ul style="list-style-type: none"> • 1US Quart – (0.945 liters) • 1US Gallon – (3.785 liters) • 1US Drum – (18.925 liters)
<p>Finish Flat 1/10</p>	<p>Transportation & Storage Care should be taken to avoid spillage. Protect from frost & humidity.</p>
<p>Coverage Approximately 10-11 square meters per liter.</p>	
<p>Drying Time Touch-dry in 2 hours Re-coatable after 4-6 hours</p>	
<p>Thinner White spirit, Colors UNDERCOAT could be also diluted with thinner to shorten the drying time. Thin up to 10%-20%</p>	

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.
Tel: 961 1 303414-305649-306966-819672 Beirut-Lebanon. Fax: 961-1-816428. E-mail: kassaa@kassaa.com .