



Product Name URETHANE flat	Preparation All surfaces to be painted should be clean , dry and free from loose & flaking material. Rub down & apply a diluted coat as primer.
Technical Name Smooth flat varnish 1 pack urethane based	Instructions Stir well. Easy to apply by brush , roller or airless spray. Do not apply when rain is expected.
Key Properties <ul style="list-style-type: none"> • Transparent • Unleaded • UV resistant, contains a special light stabilizer for enhanced protection against harsh atmospheric exposure • Good durability, fading and yellowing resistance • Provides a water repellent film • Could be applied on wooden floors for protection against traffic • Ideal for universal surfaces protection (Glazing etc.) • 72 attractive wood colors available through the automated tinting system. 	Cleaning Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly. Do not empty product into drains or watercourses.
Recommended Uses Internal & external applications	Additional Info Product batches are tested using a quality control system. Colors URETHANE flat is a low odor product.
Type of Substrate Smooth, planed softwood & hardwood...	Pack Size <ul style="list-style-type: none"> • 1US Quart – (0.945 liters) • 1US Gallon – (3.785 liters)
Finish flat	Transportation & Storage Care should be taken to avoid spillage. Protect from frost & humidity.
Coverage Approximately 10-12 square meters per liter.	
Drying Time Touch-dry in 4-6 hours Re-coatable after 16-24 hours	
Thinner White spirit, URETHANE flat could be also diluted with thinner to shorten the drying time. Thin up to 10%-20%	

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.
 Tel: 961 1 303414-305649-306966-819672 Beirut-Lebanon . Fax:961-1-816428 . E-mail: kassaa@kassaa.com .