



<b>Product Name</b> URETHANE semi gloss	<b>Preparation</b> All surfaces to be painted should be clean , dry and free from loose & flaking material. Rub down & apply a diluted coat as primer.
<b>Technical Name</b> Semi-gloss varnish 1 pack urethane based	<b>Instructions</b> Stir well. Easy to apply by brush , roller or airless spray. Do not apply when rain is expected.
<b>Key Properties</b> <ul style="list-style-type: none"> <li>• Transparent</li> <li>• Unleaded</li> <li>• UV resistant, contains a special light stabilizer for enhanced protection against harsh atmospheric exposure</li> <li>• Very good durability, fading and yellowing resistance</li> <li>• Provides a water repellent film</li> <li>• Could be applied on wooden floors for protection against traffic</li> <li>• Ideal for universal surfaces protection (Glazing etc.)</li> <li>• 72 attractive wood colors available through the automated tinting system.</li> </ul>	<b>Cleaning</b> Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly. Do not empty product into drains or watercourses.
<b>Recommended Uses</b>	<b>Additional Info</b> Product batches are tested using a quality control system. Colors URETHANE semi gloss is a low odor product.
<b>Type of Substrate</b> Smooth, planed softwood & hardwood...	<b>Pack Size</b> <ul style="list-style-type: none"> <li>• 1US Quart – (0.945 liters)</li> <li>• 1US Gallon – (3.785 liters)</li> </ul>
<b>Finish</b> semi gloss	<b>Transportation &amp; Storage</b> Care should be taken to avoid spillage. Protect from frost & humidity.
<b>Coverage</b> Approximately 10-12 square meters per liter.	
<b>Drying Time</b> Touch-dry in 4-6 hours Re-coatable after 16-24 hours	
<b>Thinner</b> White spirit, URETHANE semi gloss could be also diluted with thinner to shorten the drying time. Thin up to 10%-20%	

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.  
 Tel: 961 1 303414-305649-306966-819672 Beirut-Lebanon . Fax:961-1-816428 . E-mail: [kassaa@kassaa.com](mailto:kassaa@kassaa.com) .