

**Product Name**

FIXATEUR

Technical Name

A synthetic one component solution for porous or friable surfaces

Key Properties

- Binds friable & chalking surfaces
- Highly penetrating
- To be used under water borne systems
- Transparent
- Concentrated
- Can be recoated even after long atmospheric exposure

Recommended Uses

Suitable as a stabilizer to all friable nature surfaces

Type of Substrate

Concrete, stone, brick...

Finish

N/A

Coverage

8m²/lt

Drying Time

Touch-dry in 2 hour
Recoatable overnight

Thinner

White spirit or thinner up to 50%.

Preparation

All surfaces to be painted should be clean & dry

Instructions

Easy to apply by brush, roller or airless spray.
Do not apply when rain is expected.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly.
Do not empty product into drains or watercourses.

Additional Info

Product batches are tested using a quality control system.

Pack Size

- 1US Quart (0.945 liters)
- 1US Gallon (3.785 liters)
- 1US Drum (18.925 liters)

Transportation & Storage

Care should be taken to avoid spillage. Protect from frost & humidity.

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.

Tel-303414-305649-306966-819672 Beirut-Lebanon . Fax:961-1-816428 . e-mail: kassaa@kassaa.com .