



Product Name

Floor Paint

Technical Name

A High build, one pack synthetic urethane floor coating.

Key Properties

- Resistant to water
- Resistant to splashes of mild chemicals
- Gloss finish
- Can be supplied with a slip resistant additive
- Self priming
- Excellent color & gloss retention

Recommended Uses

Ideal as a top finish for interior & exterior concrete & steel floors subject to light traffic:

- Parking
- Warehouses
- Factories
- Hospitals & schools
- Public buildings
- Airports & Hotels
- Shopping centers
- Sports facilities

Type of Substrate

Concrete, steel floors etc.

Finish

Full gloss.

Coverage

8m²/lt for a dry film thickness of 75mic.
 6.4m²/lt for a dry film thickness of 100mic.
 4.3m²/lt for a dry film thickness of 150mic.

Drying Time

Touch-dry in 2 hour
 Full cure 7 days

Thinner

White spirit,
 Thin up to 25% for airless spraying.
 Thin up to 15% for brush & roller applications.
 Thinner could be used as solvent.

Preparation

All surfaces to be painted should be clean, dry and free from loose & flaking material. Rub down & apply a diluted coat of Floor paint as primer.

Instructions

Stir well.
 Easy to apply by brush, roller or airless spray. Do not apply when rain is expected.
 Applications should be in accordance with BS6150 & BS5493 standards.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with Super thinner & rinse thoroughly.
 Do not empty product into drains or watercourses.

Additional Info

Product batches are tested using a quality control system.

Pack Size

- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).
- 1US Drum – (18.925 liters).

Transportation & Storage

Care should be taken to avoid spillage. Protect from frost & humidity.