



Product Name

Acrylic Floor Paint

Technical Name

A High build , one pack water acrylic floor coating.

Key Properties

- Resistant to water
- Resistant to splashes of mild chemicals
- Silk finish
- Can be supplied with a slip resistant additive
- Self priming
- Excellent color retention
- Rubberized

Recommended Uses

Ideal as a top finish for interior & exterior concrete & steel floors subject to light traffic:

- Parking
- Warehouses
- Factories
- Hospitals & schools
- Public buildings
- Airports & Hotels
- Shopping centers
- Sports facilities

Type of Substrate

Concrete floors etc.

Finish

Silk finish

Coverage

10m²/lt for a dry film thickness of 75mic.
8m²/lt for a dry film thickness of 100mic.
6m²/lt for a dry film thickness of 150mic.

Drying Time

Touch-dry in 2 hours
Full cure 4 days

Thinner

Water,
Thin up to 25% for airless spraying.
Thin up to 15% for brush & roller applications.

Preparation

All surfaces to be painted should be clean , dry and free from loose & flaking material. Rub down & apply a diluted coat of Acrylic Floor paint as primer.

Instructions

Stir well.
Easy to apply by brush , roller or airless spray.
Do not apply when rain is expected.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm water & rinse thoroughly.
Do not empty product into drains or watercourses.

Additional Info

Product batches are tested using a quality control system.
Oxford Acrylic floor paint is a highly elastic product

Pack Size

- 1 US Quart – (0.945 liters).
- 1 US Gallon – (3.785 liters).
- 1 US Drum – (18.925 liters).

Transportation & Storage

Care should be taken to avoid spillage. Protect from frost & humidity.