



Product Name

FLUO

Technical Name

Synthetic based fluorescent paint

Key Properties

- The FLUO range of daylight fluorescent colors is used to add maximum visual impact in a huge variety of applications.
- 7 colors available.
- Excellent Resistance to atmospheric exposure.
- Excellent color & gloss retention.
- All fluorescent pigments used in the production of FLUO comply to the UK "safety of toys" BSEN 71-3:1995 part 3 and the European EN 71-3:1994 "safety of toys" part 3: "Migration of certain elements".

Recommended Uses

FLUO could be used on interior as well as exterior surfaces.

Type of Substrate

Fluorescent colors are translucent, they should be applied over a white undercoat to obtain the maximum effect.

Finish

Gloss.

Coverage

10 M2/LT for a dry film thickness of 50mic.

Drying Time

Touch-dry in 2 hour

Thinner

White spirit or thinner up to 5%.
Minimum dilution is required for best results.

Preparation

All surfaces to be painted should be clean, dry and free from loose & flaking material. Rub down & prime with a white undercoat, then apply FLUO.

Two thick coats of paints are recommended, each a minimum of 50 microns dry film.

Instructions

Stir well.

Easy to apply by brush, roller or airless spray. Do not apply when rain is expected.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly.

Do not empty product into drains or watercourses.

Additional Info

Product batches are tested using a quality control system.

Pack Size

- 1pack (0.5 liters)
- 1 US gallon (3.76 liters)

Transportation & Storage

Care should be taken to avoid spillage. Protect from frost & humidity.