



Product Name

Heat Resisting Paint

Technical Name

A synthetic solvent based protective coating for heated surfaces

Key Properties

- Resistant to high levels of temperatures (100C)
- Two attractive colors: Black, Aluminum - other colors on request.

Recommended Uses

Ideal as a top finish for interior & exterior surfaces:

- Exhausts
- Stoves

Type of Substrate

Steel, concrete surfaces etc.

Finish

Black color – flat finish
Aluminum – Metallic silk finish

Coverage

Approximately 10 square meters per liter.

Drying Time

Touch-dry in 2 hours

Thinner

White spirit,
Thin up to 15% for airless spraying.
Thin up to 10% for brush & roller applications.

Preparation

All surfaces to be painted should be clean, dry and free from loose & flaking material. Rub down & apply a diluted coat of Heat Resisting paint as primer.

Instructions

Stir well.
Easy to apply by brush, roller or airless spray.
Do not apply when rain is expected.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly.
Do not empty product into drains or watercourses.

Additional Info

Product batches are tested using a quality control system.

Do not apply Heat resisting paint on surfaces subject to direct flames

Pack Size

- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).
- 1US Drum – (18.925 liters).

Transportation & Storage

Care should be taken to avoid spillage. Protect from frost & humidity.

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.

Tel-303414-305649-306966-819672 Beirut-Lebanon . Fax:961-1-816428 . e-mail: kassaa@kassaa.com .