

**Product Name**

MARINE PAINT PRIMER

Technical Name

A one component primer for marine vessels

Key Properties

- Excellent Resistance to atmospheric exposure & salts
- Excellent color & gloss retention
- None chalking, none yellowing.
- Tough & abrasion resistant
- Can be recoated even after long atmospheric exposure
- Resistant to mineral and vegetable oils, white spirit, paraffin & aliphatic, petroleum products
- Resistant to splash of mild chemicals

Recommended Uses

Suitable for marine atmosphere exposure and immersions

Type of Substrate

Formulated to have high grip on all metal & wood substrates

Finish

Flat.

Coverage

5m²/lt for a dry film thickness of 100mic.

Drying Time

Touch-dry in 2 hour

Thinner

White spirit or N/C thinner up to 15%.

Preparation

All surfaces to be painted should be clean, dry and free from loose & flaking material. Rub down & apply.

Instructions

Stir well.
Easy to apply by brush, roller or airless spray.
Do not apply when rain is expected.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with super thinner & rinse thoroughly.
Do not empty product into drains or watercourses.

Additional Info

Product batches are tested using a quality control system.

Pack Size

- 1US Quart (0.945 liters)
- 1US Gallon (3.785 liters)
- 1US Drum (18.925 liters)

Transportation & Storage

Care should be taken to avoid spillage. Protect from frost & humidity.