



Product Name

Road Marking

Technical Name

One pack quick drying floor coating

Key Properties

- Can be supplied with a slip resistant additive
- Self priming
- Excellent color & gloss retention
- Good adhesion
- Excellent abrasion resistance
- Light reflection properties can be increased by addition of glass beads
- Resistant to water, oil and brine

Recommended Uses

Suitable for application as a universal marking paint on asphalt, concrete, brick, on roads, runways, car parks, and sport facilities.

Type of Substrate

Concrete, bitumen, steel floors etc.

Finish

Full gloss.

Coverage

8m²/lt for a dry film thickness of 75mic.
 6.4m²/lt for a dry film thickness of 100mic.
 4.3m²/lt for a dry film thickness of 150mic.

Drying Time

Touch-dry in 2 hour
 Full cure 7 days

Thinner

Xylene or thinner,
 Thin up to 25% for airless spraying.
 Thin up to 15% for brush & roller applications.

Preparation

All surfaces to be painted should be clean, dry and free from loose & flaking material. Apply directly on the substrate.

Instructions

Stir well.
 Easy to apply by brush, roller or airless spray.
 Do not apply when rain is expected.
 Applications should be in accordance with BS6150 & BS5493 standards.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with Super thinner & rinse thoroughly.
 Do not empty product into drains or watercourses.

Additional Info

Product batches are tested using a quality control system.

Pack Size

- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).
- 1US Drum – (18.925 liters).

Transportation & Storage

Care should be taken to avoid spillage. Protect from frost & humidity.