

**Product Name**

OXIBOND 4001

**Technical Name**

Plastic screen for protection against all atmospheric influences

**Key Properties**

- A premium quality water & damp repellent
- Provides excellent exterior protection against all atmospheric influences
- Suitable to be applied on interior surfaces wherever extra protection & washable surfaces are needed
- Offers enhanced resistance to flame spread
- Will stop the growth of moulds & fungi
- Very low VOC content
- The film formed by Oxibond 4001 will withstand traffic

**Recommended Uses**

Exterior – Interior applications

**Type of Substrate**

Plaster , embossed wall coverings , gypsum board , concrete , cement rendering , brickwork , block work , natural stones , exterior textured finishes , smooth finishes etc.

**Finish**

Colorless eggshell luster

**Coverage**

Approximately 10 square meters per liter.

**Drying Time**

Touch-dry in 1 hour

**Thinner**

Clean water.

Exterior applications:

Thin up to 50% max. for the first coat.

Thin up to 25% max. for the following coats

Interior applications:

Oxibond could be thinned up to 100% dependant on the gloss required

**Preparation**

All surfaces to be painted should be clean , dry and free from loose & flaking material. Rub down & rinse. No primer is required.

**Instructions**

Stir well. Easy to apply by brush , roller or airless spray. Do not apply on damp surfaces , at temperatures below 5C or when rain is expected in the next 48 hours.

**Cleaning**

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water & rinse thoroughly. Do not empty product into drains or watercourses.

**Additional Info**

- Contains no added lead.
- Product batches are tested using a quality control system.
- Oxibond 4001 is a milky white liquid that will dry to form a colorless film.
- The film formed is highly elastic

**Pack Size**

- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).
- 1US Drum – (18.925 liters).

**Transportation & Storage**

Care should be taken to avoid spillage. Protect

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.

Tel:303414-305649-306966-819672 Beirut-Lebanon . Fax:961-1-816428 . e-mail: [kassaa@kassaa.com](mailto:kassaa@kassaa.com) .