



Product Name

OXIBOND 4003

Technical Name

Plastic screen for protection against all atmospheric influences

Key Properties

- A premium quality water & damp repellent – Formulated to withstand very low temperatures & snow accumulation
- Provides excellent exterior protection against all atmospheric influences
- Suitable to be applied on interior surfaces wherever extra protection & washable surfaces are needed
- Offers enhanced resistance to flame spread
- Will stop the growth of moulds & fungi
- Very low VOC content
- Ideal for use as a protective coating on cement parking floors as well as all kind of wood floors
- Excellent adhesive

Recommended Uses

Exterior – Interior applications

Type of Substrate

Plaster , embossed wall coverings , gypsum board , concrete , cement rendering , brickwork , block work, natural stones , exterior textured finishes , smooth finishes etc.

Finish

Colorless eggshell luster

Coverage

Approximately 10 square meters per liter.

Drying Time

Touch-dry in 1 hour
Re-coatable after 2-3 hours

Thinner

Clean water.

Exterior applications:

Thin up to 50% max. for the first coat.

Thin up to 25% max. for the following coats

Interior applications:

Oxibond could be thinned up to 100% dependant on the gloss required

Preparation

All surfaces to be painted should be clean , dry and free from loose & flaking material. Rub down & rinse. No primer is required.

Instructions

Stir well. Easy to apply by brush, roller or airless spray. Do not apply on damp surfaces, at temperatures below 5C or when rain is expected in the next 48 hours.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water & rinse thoroughly. Do not empty product into drains or watercourses.

Additional Info

- Contains no added lead.
- Product batches are tested using a quality control system.
- Oxibond 4003 is a milky white liquid that will dry to form a colorless film.
- The film formed is highly elastic

Pack Size

- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).
- 1US Drum – (18.925 liters).

Transportation & Storage

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.
Tel-303414-305649-306966-819672 Beirut-Lebanon . Fax:961-1-816428 . e-mail: kassaa@kassaa.com .