



**Product Name**

OXIBOND 4004

**Technical Name**

Plastic cement additive for protection against all atmospheric influences

**Key Properties**

- A premium quality water & damp repellent
- Provides excellent exterior protection against all atmospheric influences
- Especially formulated as a quick soluble additive into all kind of cement mixes
- Offers enhanced resistance to flame spread
- Will stop the growth of moulds & fungi
- Very low VOC content
- Could be used to help the grip of new cement mix over old surfaces

**Recommended Uses**

Exterior – Interior applications

**Type of Substrate**

Could be mixed with all kinds of cement, plaster, powder putty etc.

**Finish**

N/A

**Coverage**

N/A

**Drying Time**

Oxibond 4004 will dry normally with the cement mix

**Thinner**

Mix with cement & powder putty as supplied in containers

**Preparation**

Oxibond 4004 could be added to the water used in the cement mix

**Instructions**

Add from 200gr to 1kg per 50kgs of cement, plaster, or powder putty

**Cleaning**

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water & rinse thoroughly. Do not empty product into drains or watercourses.

**Additional Info**

- Contains no added lead.
- Product batches are tested using a quality control system.
- Oxibond 4004 is highly elastic

**Pack Size**

- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).
- 1US Drum – (18.925 liters).

**Transportation & Storage**

Care should be taken to avoid spillage. Protect from frost & humidity.