



Product Name

OXIBOND 4005

Technical Name

Plastic screen for protection against all atmospheric influences

Key Properties

- A premium quality water & damp repellent
- Provides excellent protection against all atmospheric influences
- Suitable to be applied on interior surfaces wherever extra protection & washable surfaces are needed
- Offers enhanced resistance to flame spread
- Will stop the growth of moulds & fungi
- Very low VOC content
- Specially formulated for the application over glazed surfaces as well as over Textured finishes etc.

Recommended Uses

Exterior – Interior applications

Type of Substrate

Plaster, embossed wall coverings, gypsum board, concrete , cement rendering , brickwork , block work, natural stones , exterior textured finishes , smooth finishes, glaze etc.

Finish

Colorless eggshell luster

Coverage

Approximately 10 square meters per liter.

Drying Time

Touch-dry in 1 hour
 Re-coatable after 2-3 hour
 Full cure 24 hours

Thinner

Clean water.
 Oxibond could be thinned up to 200% dependant on the gloss required

Preparation

All surfaces to be painted should be clean , dry and free from loose & flaking material. Rub down & rinse. No primer is required.

Instructions

Stir well. Easy to apply by brush , roller or airless spray. Do not apply on damp surfaces , at temperatures below 5C or when rain is expected in the next 48 hours.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water & rinse thoroughly. Do not empty product into drains or watercourses.

Additional Info

- Contains no added lead.
- Product batches are tested using a quality control system.
- Oxibond 4005 is a milky white liquid that will dry to form a colorless film.
- The film formed is highly elastic
- Oxibond 4005 flat is available upon request

Pack Size

- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).
- 1US Drum – (18.925 liters).

Transportation & Storage

Care should be taken to avoid spillage. Protect from frost & humidity.