

**Product Name**

OXIBOND 4006

**Technical Name**

Alkyl based Poly-Siloxane oligomer  
(Silicone based)

**Key Properties**

- A premium quality water & damp repellent by capillary action
- Does not change the substrate's natural porosity and look
- Prevents rain and run-off water penetrating walls and facades, whilst allowing substrates to breath
- Outstanding resistance to aging agents (Freeze, U.V, etc.) due to the stable structure of the Siloxane bonds that form with the substrate's reactive groups
- Excellent penetration power in all standard materials
- Quick drying on all neutral and alkaline substrates, the BEADING EFFECT is noticeable within few hours of application
- Paintability with most aqueous dispersion type paints (prior testing preferred)

**Recommended Uses**

Exterior – Interior applications

**Type of Substrate**

Rough and smooth stonework, brickwork, timber, etc...

**Finish**

No visible film is formed

**Coverage**

Approximately 0.4 liter for one square meter.

**Drying Time**

Full cure 24 hours

**Thinner**

No thinning required.

**Preparation**

All surfaces to be painted should be clean , dry and free from loose & flaking material. Clean any dirty surfaces (avoid using acidic or alkaline chemical detergents) Fill in cracks more than 0.8mm wide. It is always advisable to wait 28 days before treating fresh masonry.

**Instructions**

Stir well. Easy to apply by brush, roller or airless spray. Do not apply on damp surfaces, at temperatures below 5C or when rain is expected in the next 24 hours.

**Cleaning**

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit.

**Additional Info**

- Contains no added lead. Non toxic.
- Product batches are tested using a quality control system.

**Pack Size**

- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).
- 1US Drum – (18.925 liters).

**Transportation & Storage**

Care should be taken to avoid spillage.

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.

Tel:303414-305649-306966-819672 Beirut-Lebanon . Fax:961-1-816428 . e-mail: [kassaa@kassaa.com](mailto:kassaa@kassaa.com) .