

# OXIBOND

## WATER PROOFING

### Product Name

OXIBOND 4010

### Technical Name

Water based Lacquer protection

### Key Properties

- Totally transparent when dry
- Provides excellent protection against all atmospheric influences
- Suitable for interior & exterior surfaces where extra protection & washable surfaces are needed
- Offers enhanced resistance to flame spread
- Excellent for gold, silver & copper leaf protection as well as metallic & fluorescent paint protection
- Very low VOC content

### Recommended Uses

Exterior – Interior applications

### Type of Substrate

Plaster, embossed wall coverings, gypsum board, concrete, cement rendering, brickwork, block work, natural stones, metallic paint, smooth finishes, glaze etc.

### Finish

Colorless semi gloss

### Coverage

Approximately 10 square meters per liter.

### Drying Time

Touch-dry in 1 hour  
Re-coatable after 2-3 hour  
Full cure 48 hours

### Thinner

Clean water.  
No thinning is required.

### Preparation

All surfaces to be painted should be clean, dry and free from loose & flaking material. Rub down & rinse. No primer is required.

### Instructions

Stir well. Easy to apply by brush, roller or airless spray.  
Do not apply on damp surfaces, at temperatures below 5C or when rain is expected in the next 48 hours.

### Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water & rinse thoroughly.  
Do not empty product into drains or watercourses.

### Additional Info

- Contains no added lead.
- Product batches are tested using a quality control system.
- Oxibond 4010 is a milky white liquid that will dry to form a completely colorless film

### Pack Size

- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).
- 1US Drum – (18.925 liters).

### Transportation & Storage

Care should be taken to avoid spillage. Protect from frost & humidity