

**Product Name**

ALKYD VARNISH

Technical Name

Synthetic alkyd varnish

Key Properties

- Very attractive gloss finish
- Highly washable
- Resists cracking , flaking & peeling
- Provides a water repellent film

Recommended Uses

Interior applications

Type of Substrate

Smooth, planed softwood & hardwood.

Finish

Gloss finish

Coverage

Approximately 13 square meters per liter.

Drying TimeTouch-dry in 5 hour
Re-coatable after 16-24 hours**Thinner**

White spirit, SOIB Alkyd Varnish could be also diluted with thinner to shorten the drying time.

Thin up to 15% max.

Preparation

All surfaces to be painted should be clean , dry and free from loose & flaking material. Rub down & apply a diluted coat as primer.(Double boiled linseed oil could be also used)

Instructions

Stir well. Easy to apply by brush , roller or airless spray.

CleaningRemove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly.
Do not empty product into drains or watercourses.**Additional Info**Product batches are tested using a quality control system.
SOIB Polyurethane Varnish is a low odor product.**Pack Size**

- 1US Pint – (0.470 liters).
- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).

Transportation & Storage

Care should be taken to avoid spillage. Protect from frost & humidity.