

**Product Name**

ALUMINIUM

Technical Name

Synthetic Alkyd based bright metallic paint

Key Properties

- Incorporating flake aluminum
- Based on a high quality synthetic media
- Reflects solar radiation thus Prevents excess temperature increases
- Long term protection without maintenance
- Heat resisting

Recommended Uses

Interior & exterior applications

Type of Substrate

Suitable on storage tanks, ducting, pipe work etc. SOIB Aluminum could be also used on wood , dry plaster & masonry surfaces.

Finish

Metallic

Coverage

Approximately 9 square meters per liter.

Drying Time

Touch-dry in 5 hour
Re-coatable after 16-24 hours

Thinner

White spirit, SOIB Aluminum could be also diluted with thinner to shorten the drying time.
Thin up to 10% max.

Preparation

All surfaces to be painted should be clean, dry and free from loose & flaking material. Rub down & prime.

Instructions

Stir well. Easy to apply by brush, roller or airless spray. Do not apply when rain is expected.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly.
Do not empty product into drains or watercourses.

Additional Info

Product batches are tested using a quality control system.
SOIB Aluminum is a low odor product

Pack Size

- 1US Pint – (0.470 liters).
- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).
- 1US Drum – (18.925 liters).

Transportation & Storage

Care should be taken to avoid spillage. Protect from frost & humidity.