



Product Name	CHALKBOARD
Technical Name	Synthetic Alkyd based enamel flat finish
Key Properties	<ul style="list-style-type: none">• Specially formulated for schools green Board & black board applications• Based on a high quality synthetic alkyd resin• Outstanding durability• Washable• Attractive Green & black colors
Recommended Uses	Interior applications
Type of Substrate	Wood or plaster
Finish	Dead flat
Coverage	Approximately 10 square meters per liter.
Drying Time	Touch-dry in 5 hour Re-coatable after 16-24 hours
Thinner	White spirit , SOIB Chalkboard could be also diluted with thinner to shorten the drying time. Thin up to 10% max.
Preparation	All surfaces to be painted should be clean , dry and free from loose & flaking material. Rub down & prime with one or two coats of undercoat.
Instructions	Stir well. Easy to apply by brush , roller or airless spray. Do not apply when rain is expected.
Cleaning	Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly. Do not empty product into drains or watercourses.
Additional Info	Product batches are tested using a quality control system. SOIB Chalkboard is a low odor product
Pack Size	<ul style="list-style-type: none">• 1US Quart – (0.945 liters).• 1US Gallon – (3.785 liters).
Transportation & Storage	Care should be taken to avoid spillage. Protect from frost & humidity.

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.
Tel-303414-305649-306966-819672 Beirut-Lebanon . Fax:961-1-816428 . e-mail: kassaa@kassaa.com .