



<b>Product Name</b>	EGGSHELL
<b>Technical Name</b>	Synthetic Alkyd based enamel eggshell finish
<b>Key Properties</b>	<ul style="list-style-type: none"><li>• Very attractive silk finish</li><li>• Based on a high quality synthetic alkyd resin</li><li>• Outstanding durability</li><li>• Highly washable</li><li>• Excellent gloss &amp; color retention</li></ul>
<b>Recommended Uses</b>	Interior & exterior applications
<b>Type of Substrate</b>	Wood & metal. Plaster , wallboards , concrete , cement rendering , brick work & block work etc.
<b>Finish</b>	Eggshell finish
<b>Coverage</b>	Approximately 11 square meters per liter.
<b>Drying Time</b>	Touch-dry in 5 hour Re-coatable after 16-24 hours
<b>Thinner</b>	White spirit , SOIB eggshell could be also diluted with thinner to shorten the drying time. Thin up to 10% max.

<b>Preparation</b>	All surfaces to be painted should be clean , dry and free from loose & flaking material. Rub down & prime with one or two coats of undercoat.
<b>Instructions</b>	Stir well. Easy to apply by brush , roller or airless spray. Do not apply when rain is expected.
<b>Cleaning</b>	Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly. Do not empty product into drains or watercourses.
<b>Additional Info</b>	Product batches are tested using a quality control system. SOIB Eggshell is a low odor product
<b>Pack Size</b>	<ul style="list-style-type: none"><li>• 1US Quart – (0.945 liters).</li><li>• 1US Gallon – (3.785 liters).</li></ul>
<b>Transportation &amp; Storage</b>	Care should be taken to avoid spillage. Protect from frost & humidity.

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.  
Tel-303414-305649-306966-819672 Beirut-Lebanon . Fax:961-1-816428 . e-mail: [kassaa@kassaa.com](mailto:kassaa@kassaa.com) .