

**Product Name**

FLAT

Technical Name

Synthetic Alkyd based enamel flat finish

Key Properties

- Very attractive flat finish
- Based on a high quality synthetic alkyd resin
- Outstanding durability
- Highly washable
- Excellent gloss & color retention

Recommended Uses

Interior & exterior applications

Type of Substrate

Wood & metal. Plaster , wallboards , concrete , cement rendering , brick work & block work etc.

Finish

Flat

Coverage

Approximately 10 square meters per liter.

Drying TimeTouch-dry in 5 hour
Re-coatable after 16-24 hours**Thinner**

White spirit , SOIB Flat could be also diluted with thinner to shorten the drying time.

Thin up to 10% max.

Preparation

All surfaces to be painted should be clean , dry and free from loose & flaking material. Rub down & prime with one or two coats of undercoat.

Instructions

Stir well. Easy to apply by brush , roller or airless spray. Do not apply when rain is expected.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly.

Do not empty product into drains or watercourses.

Additional InfoProduct batches are tested using a quality control system.
SOIB Flat is a low odor product**Pack Size**

- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).

Transportation & Storage

Care should be taken to avoid spillage. Protect from frost & humidity.