



Product Name N/C FLAT	Preparation All surfaces to be painted should be clean , dry and free from loose & flaking material. Rub down & prime with SOIB N/C Primer.
Technical Name Nitro Cellulose based flat finish paint	Instructions Stir well. Easy to apply by spray gun.
Key Properties <ul style="list-style-type: none">• Very attractive flat finish• Based on a high quality N/C resin• Outstanding durability• Highly washable• Excellent color retention	Cleaning Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with thinner & rinse thoroughly. Do not empty product into drains or watercourses.
Recommended Uses Interior applications	Additional Info Product batches are tested using a quality control system.
Type of Substrate Furniture, wood & metal.	Pack Size <ul style="list-style-type: none">• 1US Gallon – (3.785 liters).
Finish Flat	Transportation & Storage Care should be taken to avoid spillage. Protect from frost & humidity.
Coverage Approximately 8 square meters per liter.	
Drying Time Touch-dry in 10 minutes Re-coatable after 30 minutes	
Thinner Thin up to 100% max. N/C thinner.	

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.
Tel-303414-305649-306966-819672 Beirut-Lebanon . Fax:961-1-816428 . e-mail: kassaa@kassaa.com .