

**Product Name**

POLYURETHANE VARNISH

**Technical Name**

Synthetic Polyurethane 1-pack varnish

**Key Properties**

- Very attractive silk – flat or gloss finish
- Based on a high quality polyurethane resin
- Outstanding durability
- Highly washable
- Resists cracking , flaking & peeling
- Provides a water repellent film
- Could be applied on wooden floors for protection against traffic

**Recommended Uses**

Interior &amp; exterior applications

**Type of Substrate**

Smooth, planed softwood &amp; hardwood.

**Finish**

Gloss eggshell or flat finish

**Coverage**

Approximately 13 square meters per liter.

**Drying Time**Touch-dry in 5 hour  
Re-coatable after 16-24 hours**Thinner**White spirit, SOIB Polyurethane could be also diluted with thinner to shorten the drying time.  
Thin up to 15% max.**Preparation**

All surfaces to be painted should be clean , dry and free from loose &amp; flaking material. Rub down &amp; apply a diluted coat as primer.(Double boiled linseed oil could be also used)

**Instructions**

Stir well. Easy to apply by brush , roller or airless spray. Do not apply when rain is expected.

**Cleaning**Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly.  
Do not empty product into drains or watercourses.**Additional Info**Product batches are tested using a quality control system.  
SOIB Polyurethane Varnish is a low odor product.  
Supplied in transparent plus an attractive selection of wood colors**Pack Size**

- 1US Pint – (0.470 liters).
- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).
- 1US Drum – (18.925 liters).

**Transportation & Storage**

Care should be taken to avoid spillage. Protect from frost &amp; humidity.