

**Product Name**

POLYURETHANE PAINT

Technical Name

Synthetic Polyurethane 1-pack paint

Key Properties

- Very attractive silk – flat or gloss finish
- Based on a high quality polyurethane resin
- Outstanding durability
- Highly washable
- Resists cracking , flaking & peeling
- Provides a water repellent film
- Could be applied on floors for protection against traffic

Recommended Uses

Interior & exterior applications. Aggressive conditions.

Type of Substrate

Wood & metal. Plaster , wallboards , concrete , cement rendering , brick work & block work etc.

Finish

Gloss eggshell or flat finish

Coverage

Approximately 10 square meters per liter.

Drying TimeTouch-dry in 5 hour
Re-coatable after 16-24 hours**Thinner**

White spirit, SOIB Polyurethane could be also diluted with thinner to shorten the

Preparation

All surfaces to be painted should be clean , dry and free from loose & flaking material. Rub down & apply a diluted coat as primer.

Instructions

Stir well. Easy to apply by brush , roller or airless spray. Do not apply when rain is expected.

CleaningRemove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly.
Do not empty product into drains or watercourses.**Additional Info**Product batches are tested using a quality control system.
SOIB Polyurethane Paint is a low odor product.**Pack Size**

- 1US Pint – (0.470 liters).
- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).
- 1US Drum – (18.925 liters).

Transportation & Storage

Care should be taken to avoid spillage. Protect from frost & humidity.