

**Product Name**

RED OXIDE

**Technical Name**

Synthetic Alkyd based flat anti-corrosive primer

**Key Properties**

- Good penetration
- Based on a high quality synthetic media
- Durability & protection from rust
- Highly adhesive
- Provides an ideal surface for further coatings

**Recommended Uses**

Interior &amp; exterior applications

**Type of Substrate**

Suitable for application on iron &amp; steel.

**Finish**

Flat

**Coverage**

Approximately 9 square meters per liter.

**Drying Time**Touch-dry in 5 hour  
Re-coatable after 16-24 hours**Thinner**White spirit , SOIB Red Oxide could be also diluted with thinner to shorten the drying time.  
Thin up to 10% max.**Preparation**

All surfaces to be painted should be clean , dry and free from loose &amp; flaking material. Rub down &amp; prime.

**Instructions**

Stir well. Easy to apply by brush , roller or airless spray. Do not apply when rain is expected.

**Cleaning**Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly.  
Do not empty product into drains or watercourses.**Additional Info**Product batches are tested using a quality control system.  
SOIB Red Oxide is a low odor product**Pack Size**

- 1US Pint – (0.470 liters).
- 1US Quart – (0.945 liters).
  - 1US Gallon – (3.785 liters).
  - 1US Drum – (18.925 liters).

**Transportation & Storage**

Care should be taken to avoid spillage. Protect from frost &amp; humidity.