

**Product Name**

UNDERCOAT

Technical Name

Synthetic Alkyd based flat primer

Key Properties

- Provides an ideal finish for further coatings
- Based on a high quality synthetic alkyd resin
- Outstanding durability
- Highly adhesive on all kinds of substrates
- Low absorption

Recommended Uses

Interior & exterior applications

Type of Substrate

Wood & metal. Plaster , wallboards , concrete , cement rendering , brick work & block work etc.

Finish

Flat

Coverage

Approximately 10 square meters per liter.

Drying Time

Touch-dry in 5 hour
Re-coatable after 16-24 hours

Thinner

White spirit , SOIB Undercoat could be also diluted with thinner to shorten the drying time.
Thin up to 10% max.

Preparation

All surfaces to be painted should be clean , dry and free from loose & flaking material. Rub down & prime.

Instructions

Stir well. Easy to apply by brush , roller or airless spray. Do not apply when rain is expected.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit & rinse thoroughly.
Do not empty product into drains or watercourses.

Additional Info

Product batches are tested using a quality control system.
SOIB Undercoat is a low odor product

Pack Size

- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).
- 1US Drum – (18.925 liters).

Transportation & Storage

Care should be taken to avoid spillage. Protect from frost & humidity.