

**Product Name**

WATER BASED PAINT

Technical Name

Semi gloss water based paint

Key Properties

- Superb Opacity & outstanding durability
- Reduced dirt pick up
- Low water absorption
- Water based paint offers enhanced resistance to flame spread
- Very low VOC content
- Water based paint is odorless & highly washable

Recommended Uses

Interior & exterior applications

Type of Substrate

Plaster , wood, embossed wall coverings , gypsum board , concrete , cement rendering , brickwork & block work

Finish

Semi gloss

Coverage

Approximately 10 square meters per liter.

Drying TimeTouch-dry in 1 hour
Re-coatable after 2-4 hours**Thinner**Clean water.
Thin up to 10% max. for the first coat.
Thin up to 25%- 30% max. for the following coats**Preparation**

All surfaces to be painted should be clean , dry and free from loose & flaking material. Rub down & rinse. Prime with white water based primer or solvent based Undercoat.

Instructions

Stir well. Easy to apply by brush , roller or airless spray. Do not apply at temperatures below 5C or when rain is expected.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water & rinse thoroughly. Do not empty product into drains or watercourses.

Additional Info

- Contains no added lead.
- Product batches are tested using a quality control system

Pack Size

- 1US Quart – (0.945 liters).
- 1US Gallon – (3.785 liters).
- 1US Drum – (18.925 liters).

Transportation & Storage

Care should be taken to avoid spillage. Protect from frost & humidity.