

**Product Name**

EMULSION

Technical Name

Economical vinyl matt based emulsion

Key Properties

- Attractive matt finish
- Provides interior protection
- Produces a surface resistant to yellowing
- Offers enhanced resistance to flame spread
- Very low VOC content
- SUNNY Emulsion is odorless

Recommended Uses

Interior applications

Type of Substrate

Plaster , embossed wall coverings , gypsum board , concrete , cement rendering , brickwork & block work

Finish

Matt

Coverage

Approximately 8 square meters per liter.

Drying TimeTouch-dry in 1 hour
Re-coatable after 2-4 hours**Thinner**Clean water.
Thin up to 15% max. for the first coat.
Thin up to 25% max. for the following coats.**Preparation**

All surfaces to be painted should be clean , dry and free from loose & flaking material. Rub down & rinse. Prime with Sealer where necessary.

Instructions

Stir well. Easy to apply by brush , roller or airless spray. Do not apply at temperatures below 5C or when rain is expected.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water & rinse thoroughly. Do not empty product into drains or watercourses.

Additional Info

- Contains no added lead.
- Product batches are tested using a quality control system.

Pack Size

- 1US Gallon – (3.785 liters).
- 1US Drum – (18.925 liters).

Transportation & Storage

Care should be taken to avoid spillage. Protect from frost & humidity.

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.

Tel-303414-305649-306966-819672 Beirut-Lebanon . Fax:961-1-816428 . e-mail: kassaa@kassaa.com .