

**Product Name**

VINYL PRIMER SEALER

Technical Name

Water based vinyl penetrating solution

Key Properties

- SUNNY Sealer provides a surface suitable for further decoration with waterborne paints & putties
- Formulated for application to surfaces of a highly porous or friable nature
- Adhesive on all kind of substrates
- Low water absorption
- Offers enhanced resistance to flame spread
- Very low VOC content
- SUNNY Sealer is odorless

Recommended Uses

Interior – Exterior applications

Type of Substrate

Plaster , wall coverings , wall paper , cement , gypsum board , concrete , wood rendering , brickwork & block work

Finish

Dries flat to form an excellent bond for the subsequent coats

Coverage

Approximately 12 square meters per liter.

Drying Time

Re-coatable after 0.5 to 1 hour

Thinner

Clean water.
Thin up to 45% max.

Preparation

All surfaces to be painted should be clean , dry and free from loose & flaking material. Rub down & rinse.

Instructions

Stir well. Easy to apply by brush , roller or airless spray. Do not apply at temperatures below 5C or when rain is expected.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water & rinse thoroughly. Do not empty product into drains or watercourses.

Additional Info

- Contains no added lead.
- Product batches are tested using a quality control system.
- SUNNY Sealer is also used as a carrier in preparing vinyl putty

Pack Size

- 1US Gallon – (3.785 liters).
- 1US Drum – (18.925 liters).

Transportation & Storage

Care should be taken to avoid spillage. Protect from frost & humidity.